

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO	. F	ILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/099,659		03/15/2002	Jeffrey A. Tilton	25102A	2971
22889	7590	11/28/2005		EXAM	INER
OWENS (BOYD, JENNIFER A		
2790 COLI GRANVIL			ART UNIT	PAPER NUMBER	
	,			1771	

DATE MAILED: 11/28/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

	,/						
	Application No.	Applicant(s)					
	10/099,659	TILTON, JEFFREY A.					
Office Action Summary	Examiner	Art Unit					
	Jennifer A. Boyd	1771					
The MAILING DATE of this communication a	appears on the cover sheet v	vith the correspondence address					
A SHORTENED STATUTORY PERIOD FOR REI WHICHEVER IS LONGER, FROM THE MAILING - Extensions of time may be available under the provisions of 37 CFR after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory peri - Failure to reply within the set or extended period for reply will, by sta Any reply received by the Office later than three months after the may earned patent term adjustment. See 37 CFR 1.704(b).	B DATE OF THIS COMMUN R 1.136(a). In no event, however, may a riod will apply and will expire SIX (6) MC atute, cause the application to become a	IICATION. a reply be timely filed DNTHS from the mailing date of this communication. ABANDONED (35 U.S.C. § 133).					
Status							
1)⊠ Responsive to communication(s) filed on 02	2 September 2005.						
, ,	·						
3) Since this application is in condition for allow		tters, prosecution as to the merits is					
	closed in accordance with the practice under Ex parte Quayle, 1935 C.D. 11, 453 O.G. 213.						
Disposition of Claims							
4) ⊠ Claim(s) <u>1, 5 - 7 and 9 - 28</u> is/are per 4a) Of the above claim(s) is/are without 5) □ Claim(s) is/are allowed. 6) ⊠ Claim(s) <u>1, 5 - 7 and 9 - 28</u> is/are rejected 7) □ Claim(s) is/are objected to. 8) □ Claim(s) are subject to restriction and	drawn from consideration.						
Application Papers							
9) The specification is objected to by the Exam	iner.						
10) The drawing(s) filed on is/are: a) accepted or b) objected to by the Examiner.							
Applicant may not request that any objection to t	the drawing(s) be held in abeya	ance. See 37 CFR 1.85(a).					
Replacement drawing sheet(s) including the corr	rection is required if the drawin	g(s) is objected to. See 37 CFR 1.121(d).					
11)☐ The oath or declaration is objected to by the	Examiner. Note the attache	ed Office Action or form PTO-152.					
Priority under 35 U.S.C. § 119							
12) Acknowledgment is made of a claim for fore a) All b) Some * c) None of: 1. Certified copies of the priority docume 2. Certified copies of the priority docume 3. Copies of the certified copies of the p application from the International Bure * See the attached detailed Office action for a line	ents have been received. ents have been received in priority documents have been reau (PCT Rule 17.2(a)).	Application No n received in this National Stage					
Attachment(s)	_						
 Notice of References Cited (PTO-892) Notice of Draftsperson's Patent Drawing Review (PTO-948) 		Summary (PTO-413) o(s)/Mail Date					
Notice of Dransperson's Patent Drawing Review (P10-948) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/Paper No(s)/Mail Date		Informal Patent Application (PTO-152)					

Application/Control Number: 10/099,659 Page 2

Art Unit: 1771

DETAILED ACTION

Response to Amendment

- 1. The Applicant's Amendments and Accompanying Remarks, filed September 2, 2005, have been entered and have been carefully considered. Claims 1 and 27 are amended, claims 2 4, 8 and 29 are cancelled and claims 1, 5 7 and 9 28 are pending. In view of Applicant's amendments to independent claims 1 and 27 eliminating the term "about" before the limitation of "18 22 microns", the Examiner has revised the previously applied rejection as being obvious over Goettmann below. The present invention as currently is unpatentable for reasons herein below.
- 2. The text of those sections of Title 35, U.S. Code not included in this action can be found in a prior Office action.

Claim Rejections - 35 USC § 103

3. Claims 1, 5-7 and 9-28 are rejected under 35 U.S.C. 103(a) as being unpatentable over Goettmann (US 5,851,355).

Goettmann is directed to a nonwoven composite web useful as a support for a reverse osmosis membrane (column 1, lines 5-10).

As to claims 1 and 27, Goettmann teaches a composite material comprising polymeric staple fibers, a first fiber consisting of, at least in part, of a first thermoplastic binder material which melts at a temperature less than the melting temperature of the polymeric staple fibers, and a second binder fiber consisting of, at least in part, of a second thermoplastic binder material

Application/Control Number: 10/099,659 Page 3

Art Unit: 1771

which melts at a second melting temperature less than the first melting temperature (column 2, lines 40 – 55). Goettmann teaches that the composite material comprises 5 to 40% by weight of a first polyester staple fiber, 0 to 60% by weight of a second polyester staple fiber, 15 to 50% by weight of a first thermoplastic binder fiber and 1 to 10% by weight of a second thermoplastic binder fiber (column 3, lines 55 – 68). Goettmann teaches that the first and second thermoplastic binder fibers are sheath-core bicomponent fibers (column 2, lines 55 – 65). The Examiner equates the polymeric staple fibers to Applicant's "staple fibers", the first thermoplastic binder material to Applicant's "high melt bicomponent fibers" and the second thermoplastic binder material to Applicant's "low melt bicomponent fibers". Goettmann teaches that the first and second bicomponent binder fibers has a co-polyester sheath and a polyester core (column 2, lines 55 – 65). It is known in the art that Kuraray EP-101 fibers and N-720H fibers (column 4, lines 1 – 20) comprise polyethylene terephthalate as the polyester component.

As to claims 9, 12 and 13, Goettmann teaches that the staple fibers comprise polyester fibers (column 2, lines 55 - 60).

As to claims 14 - 15 and 17 - 18, Goettmann teaches that the first and second bicomponent binder fibers have a co-polyester sheath and a polyester core (column 2, lines 55 – 65). It is known in the art that Kuraray EP-101 fibers and N-720H fibers (column 4, lines 1 – 20) comprise polyethylene terephthalate as the polyester component.

As to claims 16, 19 and 28, Goettmann teaches that the second thermoplastic binder fibers, or "low melt bicomponent fibers", have a co-polyester sheath that melts at 225°F (107.2°C) (column 2, lines 55 – 65). Goettmann teaches that the first thermoplastic binder fibers,

Application/Control Number: 10/099,659 Page 4

Art Unit: 1771

or "high melt bicomponent fibers", have a co-polyester sheath that melts at $375^{\circ}F$ (190.5°C) (column 2, lines 60 - 65).

As to claims 1, 5 and 27, Goettmann discloses the claimed invention except for that the average fiber diameter of the low melt bicomponent fiber, the high melt bicomponent fiber and staple fiber have a diameter between 18-22 microns as required by claim 1, the average diameter is between 18 - 30 microns as required by claim 27, the low melt bicomponent fiber is present in the amount of 20 - 60% by weight as required by claims 1 and 27 and that the density is between about 1.0 - 10 pcf as required by claims 5 and 27. It should be noted that the amount of low melt bicomponent fibers, fiber diameter and density are result effective variables. Goettmann teaches that variations and modifications of the composition may be devised and are within the scope and spirit of the invention. Goettmann teaches that it would be obvious to one of ordinary skill in the art that the range and blend of bicomponent fibers may be varied to effect the desired physical properties. Goettmann teaches that the physical properties (i.e., density) as well as the performance of the sheet material can be altered to fit a particular set of physical specifications (column 6, lines 18-43). Additionally, it is known in the art to adjust the fiber diameter of the composition in order to adjust the properties of the composite. It should be noted that Goettmann positively requires that the staple fibers be within the range of 0.2 to 3.0 denier (column 3, lines 5-10). In the Remarks submitted on 5/28/05, the Applicant submits that the denier range of 0.2 - 3.0 denier is equivalent to a diameter of 4.5 - 17.6 microns, which touches Applicant's claimed range when rounded. It would have been obvious to one having ordinary skill in the art at the time the invention was made to create an insulating material that the average

Application/Control Number: 10/099,659

Art Unit: 1771

fiber diameter of the low melt bicomponent fiber, the high melt bicomponent fiber and staple fiber have a diameter between about 18 – 22 microns as required by claim 1, the average diameter is between 18 – 30 microns as required by claim 27, the low melt bicomponent fiber is present in the amount of 20 – 60% by weight as required by claims 1 and 27 and that the density is between about 1.0 – 10 pcf as required by claims 5 and 27, since it has been held that discovering an optimum value of a result effective variable involves only routine skill in the art. *In re Boesch*, 617 F.2d 272, 205 USPQ 215 (CCPA 1980). In the present invention, one would have been motivated to optimize the average fiber diameter, percentage of low melting bicomponent fibers and density to create an insulating material with optimal strength and flexibility having the desired performance of the final product.

As to claims 5-7, 10-11 and 21-26, although Goettmann does not explicitly teach the claimed flexural strength of between about 40-1200 psi as required by claim 5, the material has the acoustical absorption coefficients as shown in claims 6, 10 and 21-26, the material has thermal conductivity value of between about 0.20 and 0.30 at 2 pcf density as required by claims 7 and 11, it is reasonable to presume that the claimed flexural strength of between about 40-1200 psi as required by claim 5, the material has the acoustical absorption coefficients as shown in claims 6 and 10, the material has thermal conductivity value of between about 0.20 and 0.30 at 2 pcf density as required by claims 7 and 11 and the acoustical absorption coefficients as shown in claims 21-26 is inherent to Goettmann. Support for said presumption is found in the use of like materials (i.e. a nonwoven material comprising polyester staple fibers and two types of polyester/copolyester bicomponent fibers in the desired proportions and fiber diameter ranges)

Art Unit: 1771

which would result in the claimed property. The burden is upon the Applicant to prove otherwise. *In re Fitzgerald* 205 USPQ 594. In addition, the presently claimed property of flexural strength of between about 40 – 1200 psi as required by claim 5, the material has the acoustical absorption coefficients as shown in claims 6 and 10, the material has thermal conductivity value of between about 0.20 and 0.30 at 2 pcf density as required by claims 7 and 11 and the acoustical absorption coefficients as shown in claims 21 – 26 would obviously have been present once the Goettmann product is provided. Note *In re Best*, 195 USPQ at 433, footnote 4 (CCPA 1977).

As to claim 20, Goettmann discloses the claimed invention except for that the high melt bicomponent fiber can be substituted in part or whole by crystalline/semi-crystalline bicomponent fibers having a melt flow temperature of about 150 to about 180 degrees Celsius. It would have been obvious to one having ordinary skill in the art at the time the invention was made to replace the high melt bicomponent fibers in part or in whole with crystalline/semi-crystalline bicomponent fibers since it has been held to be within the general skill of a worker in the art to select a known material on the basis of its suitability for the intended use as a matter of design choice. *In re Leshin*, 125 USPQ 416. Goettmann teaches that binder fibers different than those specified may be used, so long as the binder fiber contains thermoplastic material having a melting point lower than that of the polyester fibers and providing adequate bonding of those polyester fibers to form a non-woven web with a high tensile strength (column 6, lines 28 – 35). In the present invention, one would have been motivated to replace the high melt bicomponent fiber in part or whole with crystalline/semi-crystalline bicomponent fibers having a melt flow

Art Unit: 1771

temperature of about 150 to about 180 degrees Celsius due to the desire to increase the range of applications of the composite material.

Response to Arguments

4. Applicant's arguments filed September 2, 2005 have been fully considered but they are not persuasive.

Applicant argues that Goettmann does not teach incorporating 20 – 60% by weight of low melt bicomponent fibers. The Examiner has submitted that it would have been obvious to optimize the amount of low melt bicomponent fibers. Goettmann provides support to adjust various parameters such as the amount of bicomponent fibers. Goettmann teaches that it would be obvious to one of ordinary skill in the art that the range and blend of bicomponent fibers may be varied to effect the desired physical properties (column 6, lines 18 – 43). Absent any unexpected results for Applicant's claimed range, the Examiner submits that it is obvious to optimize the amount of bicomponent fibers to 20 – 60% by weight of the insulating material.

Applicant argues that Goettmann does not teach an average fiber diameter of 18-22 microns. In the Remarks submitted on 5/28/05, the Applicant submits that the denier range of 0.2-3.0 denier is equivalent to a diameter of 4.5-17.6 microns, which touches Applicant's claimed range when rounded. Goettmann provides support to adjust various parameters in order to tailor the desired physical properties (column 6, lines 18-43). Absent any unexpected results for Applicant's claimed range, the Examiner submits it is obvious to optimize the diameter of the polyester staple fibers. Applicant argues that Goettmann teaches that the sheet porosity is an important feature. If the sheet porosity is too low, the fibers will not attach to the support

Application/Control Number: 10/099,659

Page 8

Art Unit: 1771

substrate. Conversely, if the sheet porosity is too high, the fibers penetrate the support too much and do not form a film as desired on the surface. The Examiner does agree that Goettmann does state that fiber deniers and lengths are selected to achieve the desired sheet porosity. However, it is unclear that fibers having a slightly higher diameter than desired by Goettmann would create a sheet with unsuitable porosity. Goettmann indicates that the porosity is also controlled by fiber length so the diameter of the fibers are not the only parameter that affects the porosity. Additionally, Goettmann does indicate that it is within the scope of the invention to modify various parameters based on desired physical properties. The burden is upon the Applicant to demonstrate that the use of fibers having a diameter of 18 rather than 17.8 would adversely affect the porosity of Guttmann's product. Alternatively, if the Applicant submits that the claimed fiber diameter range has unexpected results, the burden is upon the Applicant to demonstrate that the claimed ranges are not a matter of simple optimization. The Examiner highly suggests to the Applicant to submit a 37 CFR 1.132 Declaration to establish unexpected results. In the Declaration, the Applicant should compare a sufficient number of tests both inside and outside the claimed range to show the criticality of the claimed range. In re Hill, 284 F.2d 955, 128 USPQ 197 (CCPA 1960) and must compare the claimed subject matter with the closest prior art to be effective to rebut a prima facie case of obviousness.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Jennifer A. Boyd whose telephone number is 571-272-1473. The examiner can normally be reached on Monday thru Friday (8:30am - 6:00pm).

Art Unit: 1771

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Terrel Morris can be reached on 571-272-1478. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Fennifer Boyd

November 18, 2005

Makuddock
Ula C. Ruddock

Primary Examiner Tech Center 1700